

PicturePhone Hi-Lite Quick Reference Comparison Chart

Features	Benefits	Hi-Lite XLR, EXR, NXR	Hi-Lite XL, EX, NX
Multiple Line Voltage Options	Available in 110, 220-240, and 277 volts.	Yes Available in 110, 220-240, and 277 volts.	Yes Available in 110, 220-240, and 277 volts.
Multiple Control Options	Allows unit to be controlled remotely via infrared hand-unit or external dimming system.	Yes Internal (XLR), external (EXR), or non-dimming (NXR) system.	Yes Internal (XL), external (EX), or non-dimming (NX) system.
Recessed Design	Installed flush with the ceiling. Not suspended.	Yes Recessed installation.	No Monopoint suspension.
Proper Color Temperature	Participants retain natural flesh tones.	Yes Includes two 50-watt compact fluorescent T5 lamps.	Yes Includes three 36-watt compact fluorescent T5 lamps.
Flicker-free Ballast	Doesn't create extra work for the codec and fills in "dead spots" from existing light.	Yes	Yes
Low Heat	Keeps participants comfortable, unlike studio lighting.	Yes Fixture remains cool for low heat dissipation.	Yes Fixture remains cool for low heat dissipation.
(Diffused) Glare-free	Participants won't have to squint or strain their eyes.	Yes Features opal diffuser.	Yes Features opal diffuser.
Dimmable	Easily adjustable to accent and accommodate all skin tones.	Yes Built-in dimmer module with remote (XLR) or hardwired to external dimming circuit (EXR).	Yes Built-in dimmer module with remote (XL) or hardwired to external dimming circuit (EX).
Flexible Positioning	Fixture position can be adjusted to achieve the best results.	No Hardwired by an electrician like a normal light fixture.	Yes Lights can be rotated and tilted up to 180 degrees.
Versatile Mounting	Equipped for easy mounting on a suspended ceiling grid, drywall ceiling or tripod.	Yes Replaces a 2'x2' ceiling tile (or half of a 2'x4' tile) or be installed in drywall ceilings.	Yes Equipped for ceiling grid or tripod mounting.
Safety Support System	Includes safety cable kit that supports the ceiling and the fixture.	Yes Additional support provided as a precaution.	Yes Additional support provided as a precaution.
Removable Electronic Chassis	Service oriented design.	Yes	No Unit is portable.
Long Power Cord	Long cord allows light to be easily plugged-in or hardwired when installed by end-user.	No Hardwired by an electrician.	Yes Equipped with a 25 ft AC line cord.
Portability	Designed for simple relocation by end-user.	No Must be removed by a qualified electrician.	Yes Easy to relocate.
Risk-free Evaluation Period	Evaluate product performance during the risk-free trial period.	Please call.	Please call.